

Operating System

Windows 11 Pro

Mobile Computing Platform

Intel® Core™ i5-12500H Processor

Max. 4.4GHz with Intel® Turbo Boost Technology

12MB Intel® Smart Cache

Platform options

Intel® Core™ i7-1250U vPro® Processor

Max. 4.4GHz with Intel® Turbo Boost Technology

12MB Intel® Smart Cache

Intel® Core™ i7-1250U Processor

Max. 4.7GHz with Intel® Turbo Boost Technology

24MB Intel® Smart Cache

Intel® Core™ i7-1270P vPro® Processor

Max. 4.8GHz with Intel® Turbo Boost Technology

12MB Intel® Smart Cache

Intel® Core™ i7-1280P vPro® Processor

Max. 4.8GHz with Intel® Turbo Boost Technology

24MB Intel® Smart Cache

VGA Controller

Intel® Iris® X Graphics

Optional: NVIDIA® GeForce® GTX1650 4GB discrete graphics controller**

Display

11.6" IPS TFT LCD FHD (1920 x 1080)

Protection film

1,000 nits LumiBond display with Getac sunlight readable technology

Capacitive multi-touch screen

Storage & Memory

8GB DDR4

Optional: 16GB / 32GB / 64GB DDR4

256GB PCIe NVMe SSD

Optional: 512GB / 1TB / 2TB PCIe NVMe SSD

Keyboard & Buttons

LED backlit membrane keyboard

Optional: Rubber keyboard

Power button

5 tablet programmable buttons

Pointing Device

Touchscreen

Optional: Capacitive multi-touch screen (multi-touch and digitizer)

Touchpad

Optional: Dual mode touchpad (multi-touch and digitizer)

Optional: Glass touchpad with left-click and right-click buttons

Expansion Slot

Smart card reader x 1

Optional: SD card reader x 1

Optional: 1D/2D imager barcode reader

I/O Interface

SM webcam x 1

Audio in/out combo x 1

DC in Jack x 1

USB 3.2 Gen 2 Type-C x 2

Thunderbolt™ 4 Type-C x 1

LAN (RJ45) x 1

HDMI 2.0 x 1

Thunderbolt™ 4 Type-C x 1

LAN (RJ45) x 1

HDMI 2.0 x 1

Docking connector x 1

Optional: Windows Hello face-authentication FHD camera (front-facing) x 1

Optional: RF antenna pass-through for GPS, WWAN and WLAN

Optional: 8M pixels auto focus rear camera x 1

Communication Interface

10/100/1000 base-T Ethernet

Intel® Wi-Fi 6E AX211, 802.11ax

Bluetooth (v5.3)

3. Serial port (9-pin, D-sub) x 1 + External VGA (15-pin, D-sub) x 1

2. Serial port (9-pin, D-sub) x 1 + External VGA (15-pin, D-sub) x 1

3. Serial port (9-pin, D-sub) x 1 + External VGA (15-pin, D-sub) x 1

1 + 2nd LAN (RJ45) x 1

4. Serial port (9-pin, D-sub) x 1 + Display port x 1 + 2nd LAN (RJ45) x 1

5. Serial port (9-pin, D-sub) x 2 + External VGA (15-pin, D-sub) x 1

6. Serial port (9-pin, D-sub) x 2 + Display port x 1

7. Serial port (9-pin, D-sub) x 2 + External VGA (15-pin, D-sub) x 1

1 + 2nd LAN (RJ45) x 1

8. Serial port (9-pin, D-sub) x 2 + Display port x 1 + 2nd LAN (RJ45) x 1

Communication Interface

10/100/1000 base-T Ethernet

Intel® Wi-Fi 6E AX211, 802.11ax

Bluetooth (v5.3)

3. Serial port (9-pin, D-sub) x 1 + External VGA (15-pin, D-sub) x 1

2. Serial port (9-pin, D-sub) x 1 + External VGA (15-pin, D-sub) x 1

3. Serial port (9-pin, D-sub) x 1 + External VGA (15-pin, D-sub) x 1

1 + 2nd LAN (RJ45) x 1

4. Serial port (9-pin, D-sub) x 1 + Display port x 1 + 2nd LAN (RJ45) x 1

5. Serial port (9-pin, D-sub) x 2 + External VGA (15-pin, D-sub) x 1

6. Serial port (9-pin, D-sub) x 2 + Display port x 1

7. Serial port (9-pin, D-sub) x 2 + External VGA (15-pin, D-sub) x 1

1 + 2nd LAN (RJ45) x 1

8. Serial port (9-pin, D-sub) x 2 + Display port x 1 + 2nd LAN (RJ45) x 1

Security Feature

TPM 2.0

Optional: Kensington lock

Optional: Intel® vPro® Technology

Optional: Fingerprint reader

Optional: HF RFID reader**

Optional: Windows Hello face-authentication FHD camera (front-facing)

Optional: 8M pixels auto focus rear camera x 1

Dimension (W x D x H) & Weight

313 x 228 x 39mm (12.32" x 9.37" x 1.53")

2.1kg (4.63lbs)

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Power

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Dimension (W x D x H) & Weight

342 x 281 x 34.9mm (13.46" x 11.06" x 1.37")

2.32kg (5.11lbs)

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Power

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Dimension (W x D x H) & Weight

342 x 281 x 35.3mm (13.46" x 11.06" x 1.37")

2.38kg (5.25lbs)

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Power

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Dimension (W x D x H) & Weight

342 x 281 x 35.3mm (13.46" x 11.06" x 1.37")

2.38kg (5.25lbs)

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Power

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Dimension (W x D x H) & Weight

342 x 281 x 35.3mm (13.46" x 11.06" x 1.37")

2.38kg (5.25lbs)

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Power

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Dimension (W x D x H) & Weight

342 x 281 x 35.3mm (13.46" x 11.06" x 1.37")

2.38kg (5.25lbs)

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Power

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Dimension (W x D x H) & Weight

342 x 281 x 35.3mm (13.46" x 11.06" x 1.37")

2.38kg (5.25lbs)

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Power

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Dimension (W x D x H) & Weight

342 x 281 x 35.3mm (13.46" x 11.06" x 1.37")

2.38kg (5.25lbs)

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Power

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Dimension (W x D x H) & Weight

342 x 281 x 35.3mm (13.46" x 11.06" x 1.37")

2.38kg (5.25lbs)

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Power

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Dimension (W x D x H) & Weight

342 x 281 x 35.3mm (13.46" x 11.06" x 1.37")

2.38kg (5.25lbs)

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Power

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Dimension (W x D x H) & Weight

342 x 281 x 35.3mm (13.46" x 11.06" x 1.37")

2.38kg (5.25lbs)

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Power

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

LifeSupport battery swappable technology

Optional: Windows Hello face-authentication FHD camera (front-facing)

Dimension (W x D x H) & Weight

342 x 281 x 35.3mm (13.46" x 11.06" x 1.37")

2.38kg (5.25lbs)

AC adapter (90W, 100-240VAC, 50/60Hz)

